Application No.: 10/502,468

IN THE CLAIMS:

Amend the claims as follows:

1. (Currently Amended) An image processing system, comprising:

an image selecting device for selecting computer graphics in a figure corresponding to a figure of an actual object and a positional relationship between an observer, who is viewing the actual object, and the actual object;

a nimbus generating device for generating a nimbus image around a periphery of the computer graphics;

a combined image generating device for generating a combined image combining the computer graphics and the nimbus image; and

an image display processing device for displaying the combined image on an a display which is viewed by the observer so that the combined image is superimposed on the actual object:

the computer graphics having a lacking area for showing the observer a second actual object having a part which exists on the observer side than the actual object, and said nimbus generating device generating a nimbus image around a periphery of the lacking area.

2. (Currently Amended) An image processing system, comprising:

L NO THE LOSE

File No: 24530-004

Application No.: 10/502,468

an image processing device having an image selecting device for selecting computer graphics in a figure corresponding to a figure of an actual object and a positional relationship between an observer, who is viewing the actual object, and the actual object; a nimbus generating device for generating a nimbus image around a periphery of the computer graphics; a combined image generating device for generating a combined image combining the computer graphics and the nimbus image; and a combined image sending device for sending the combined image to the observer side; and

a display device having an image display processing device for displaying the combined image, which is sent from said combined image sending device, on an a display which is viewed by the observer so that the combined image is superimposed on the actual object;

the computer graphics having a lacking area for showing the observer a second actual object having a part which exists on the observer side than the actual object, and said nimbus generating device generating a nimbus image around a periphery of the lacking area.

3. (Currently Amended) An image processing system, comprising:

an image generating device for generating computer graphics in a figure corresponding to a figure of an actual object and a positional relationship between an observer, who is viewing the actual object, and the actual object;

File No: 24530-004 Application No.: 10/502,468

a nimbus generating device for generating a nimbus image around a periphery of the computer graphics;

a combined image generating device for generating a combined image combining the computer graphics and the nimbus image; and

an image display processing device for displaying the combined image on an a display which is viewed by the observer so that the combined image is superimposed on the actual object;

the computer graphics having a lacking area for showing the observer a second actual object having a part which exists on the observer side than the actual object, and said nimbus generating device generating a nimbus image around a periphery of the lacking area.

4. (Currently Amended) An image processing system, comprising:

an image processing device having an image generating device for generating computer graphics in a figure corresponding to a figure of an actual object and a positional relationship between an observer, who is viewing the actual object, and the actual object; a nimbus generating device for generating a nimbus image around a periphery of the computer graphics; a combined image generating device for generating a combined image combining the computer graphics and the nimbus image; and a combined image sending device for sending the combined image to the observer side; and

Application No.: 10/502,468

a display device having an image display processing device for displaying the combined image, which is sent from said combined image sending device, on an a display which is viewed by the observer so that the combined image is superimposed on the actual object;

the computer graphics having a lacking area for showing the observer a second actual object having a part which exists on the observer side than the actual object, and said nimbus generating device generating a nimbus image around a periphery of the lacking area.

- 5. (Original) The image processing system according to any one of claim 1 to claim 4, wherein said nimbus generating device estimates an error in measurement of a distance between the observer and the actual object, and generates based on the error the nimbus image having an adequate thickness for preventing the actual object from being seen protruding from a periphery of the computer graphics.
- 6. (Original) The image processing system according to any one of claim 1 to claim 4, wherein said nimbus generating device generates the nimbus image having an adequate thickness for not showing the observer a displacement which occurs between the actual object and the computer graphics when the actual object or the observer moves.

Application No.: 10/502,468

- 7. (Original) The image processing system according to any one of claim 1 to claim 4, further comprising a detecting device for detecting at least one of a distance and an angle between a display which is viewed by the observer and the actual object and a direction of the actual object seen from the observer.
- 8. (Original) The image processing system according to any one of claim 1 to claim 4, wherein the actual object is a humanoid robot or an animal-type robot other than a human, which can freely move.
- 9. (Original) The image processing system according to any one of claim 1 to claim 4, further comprising a communication device for receiving the computer graphics from outside via a network.
 - 10. (Canceled)
 - 11. (Currently Amended) An image processing device, comprising:

an image selecting device for selecting computer graphics in a figure corresponding to a figure of an actual object and a positional relationship between an observer, who is viewing the actual object, and the actual object;

Application No.: 10/502,468

a nimbus generating device for generating a nimbus image around a periphery of the computer graphics; and

a combined image generating device for generating a combined image combining the computer graphics and the nimbus image;

the computer graphics having a lacking area for showing the observer a second actual object having a part which exists on the observer side than the actual object, and said nimbus generating device generating a nimbus image around a periphery of the lacking area.

12. (Currently Amended) An image processing device, comprising:

an image generating device for generating computer graphics in a figure corresponding to a figure of an actual object and a positional relationship between an observer, who is viewing the actual object, and the actual object;

a nimbus generating device for generating a nimbus image around a periphery of the computer graphics; and

a combined image generating device for generating a combined image combining the computer graphics and the nimbus image;

the computer graphics having a lacking area for showing the observer a second actual object having a part which exists on the observer side than the actual object, and said nimbus generating device generating a nimbus image around a periphery of the lacking area.

1 to 1 2 20

A STATE OF THE STA

File No: 24530-004 Application No.: 10/502,468

- 13. (Original) The image processing device according to claim 11 or claim 12, wherein said nimbus generating device estimates an error in measurement of a distance between the observer and the actual object, and generates based on the error the nimbus image having an adequate thickness for preventing the actual object from being seen protruding from a periphery of the computer graphics.
- 14. (Original) The image processing device according to claim 11 or claim 12, wherein said nimbus generating device generates the nimbus image having an adequate thickness for not showing the observer a displacement which occurs between the actual object and the computer graphics when the actual object or the observer moves.
- 15. (Original) The image processing device according to claim 11 or claim 12, further comprising a detecting device for detecting at least one of a distance and an angle between a display which is viewed by the observer and the actual object and a direction of the actual object seen from the observer.

Application No.: 10/502,468

16. (Original) The image processing device according to claim 11 or claim 12, further comprising a communication device for receiving the computer graphics from outside via a network.

17. (Cancelled)

18. (Currently Amended) An image processing device, comprising:

means for selecting computer graphics in a figure corresponding to a figure of an actual object and a positional relationship between an observer, who is viewing the actual object, and the actual object;

means for generating a nimbus image around a periphery of the computer graphics; and

means for combining the computer graphics and the nimbus image;

the computer graphics having a lacking area for showing the observer a second actual object having a part which exists on the observer side than the actual object, and said means for generating a nimbus image generating a nimbus image around a periphery of the lacking area.

19. (Currently Amended) An image processing device, comprising:

Application. No.: 10/502,468

means for generating computer graphics in a figure corresponding to a figure of an actual object and a positional relationship between an observer, who is viewing the actual object, and the actual object;

means for generating a nimbus image around a periphery of the computer graphics; and

means for combining the computer graphics and the nimbus image;

the computer graphics having a lacking area for showing the observer a second actual object having a part which exists on the observer side than the actual object, and said means for generating a nimbus image generating a nimbus image around a periphery of the lacking area.

- 20. (Original) The image processing device according to claim 18 or claim 19, wherein said means for generating a nimbus image estimates an error in measurement of a distance between the observer and the actual object, and generates based on the error the nimbus image having an adequate thickness for preventing the actual object from being seen protruding from a periphery of the computer graphics.
- 21. (Original) The image processing device according to claim 18 or claim 19, wherein said means for generating a nimbus image generates the nimbus image having an

Application No.: 10/502,468

adequate thickness for not showing the observer a displacement which occurs between the actual object and the computer graphics when the actual object or the observer moves.

- 22. (Original) The image processing device according to claim 18 or claim 19, further comprising means for detecting at least one of a distance and an angle between a display which is viewed by the observer and the actual object and a direction of the actual object scen from the observer.
- 23. (Original) The image processing device according to claim 18 or claim 19, further comprising means for receiving the computer graphics from outside via a network.
 - 24. (Cancelled)
- 25. (Currently Amended) A display device, comprising an image display processing device for displaying a combined image, which is generated by combining a nimbus image generated around a periphery of computer graphics in a figure corresponding to a figure of an actual object and a positional relationship between an observer, who is viewing the actual object, and the actual object, on a display which is viewed by the observer so that the combined image is superimposed on the actual object, the computer graphics

Application No.: 10/502,468

having a lacking area for showing the observer a second actual object having a part which exists on the observer side than the actual object, and the nimbus image also existing around the lacking area.

- 26. (Cancelled)
- 27. (Cancelled)
- 28. (Cancelled)